

Centerless belt grinder - dry version with exhaust

00103364

TAS Centerless grinders - TAS 75CGX



HM TAS 75CGX a combined belt and centerless grinder for all kind of pipe and tubes with built-in double exhaust system

HM TAS 75CGX is supplied with a double built-in dust exhaust system and an attachment which can be mounted on all belt grinders with a 75x2000 mm belt and with a large grinding surface on top.

The centerless grinding attachment is easy to operate and grinds/polishes all pipes and tubes with diameters of between 6 and 120 mm.

HM TAS 75CGX centerless grinding and polishing machine is unique compared to other centerless grinders on the market because it remain a belt grinder even when the centerless grinding attachment is mounted.

It is not necessary to take off the centerless attachment when using the belt grinder for normal grinding work.

Both the contact wheel and the flat grinding surface on top are available for normal grinding and polishing even with the attachment on the machine.

Support stands are available as extra accessory for long pipes and tubes.

Product Link:

https://hmmachinery.dk/en/product/centerless-belt-grinder-dry-version-with-exhaust-679



Product Specification

Motor (HP)	4,1
Voltage	3x400V-50 Hz
Wheel size, Drive wheel (ø mm)	200x75x24
Wheel size, Contact wheel (ø mm)	200x75x20
Wheel size, Polishing wheel (ø mm)	50x150x25
Support roller (mm)	35x90x23
Gear	NMRV 030
Pipe dimension (ø mm)	6-120
With exhaust	1
Length (mm)	1050
Width (mm)	700
Height (mm)	1150
Net weight (kg)	80

Product Link:

https://hmmachinery.dk/en/product/centerless-belt-grinder-dry-version-with-exhaust-679